

## **Gewinde-Tabelle Zollgewinde grob UNC 1" = 25,4 mm**

**Flankenwinkel 55°**

© **Land – Forsttechnik Walder**

Gewinde	Gänge je inch	Außendurchmesser		Kernlochdurchmesser in mm	
		inch	mm	Bolzen	Mutter
N1-64	64		1,85	1,55	1,58
N2-56	56		2,18	1,85	1,87
N3-48	48		2,51	2,10	2,14
N4-44	44		2,84	2,35	2,38
N5-40	40		3,18	2,65	2,70
N6-32	32		3,50	2,85	2,90
N8-32	32		4,17	3,50	3,53
N10-24	24		4,83	3,90	3,95
N12-24	24		5,49	4,50	4,59
1/4"-20	20	1/4"	6,35	5,10	5,25
5/16"-18	18	5/16"	7,94	6,60	6,68
3/8"-16	16	3/8"	9,53	8,00	8,08
7/16"-14	14	7/16"	11,11	9,40	9,44
1/2"-13	13	1/2"	12,70	10,80	10,88
9/16"-12	12	9/16"	14,23	12,20	12,30
5/8"-11	11	5/8"	15,88	13,50	13,69
3/4"-10	10	3/4"	19,05	16,50	16,62
7/8"-9	9	7/8"	22,23	19,50	19,52
1"-8	8	1"	25,40	22,25	22,34
1 1/8"-7	7	1 1/8"	28,57	25,00	25,08
1 1/4"-7	7	1 1/4"	31,75	28,00	28,26
1 3/8"-6	6	1 3/8"	34,92	30,75	30,85
1 1/2"-6	6	1 1/2"	38,10	34,00	34,03
1 3/4"-5	5	1 3/4"	44,45	39,50	39,56
2"-4 1/2	4,5	2"	50,80	45,00	45,37

2 1/4"-4 1/2	4,5	2 1/4"	57,15	51,50	51,72
2 1/2"-4	4	2 1/2"	63,50	57,25	57,39
2 3/4"-4	4	2 3/4"	69,85	63,50	63,74
3"-4	4	3"	76,2	70,00	70,09
3 1/4"-4	4	3 1/4"	82,55	76,20	76,44
3 1/2"-4	4	3 1/2"	88,9	82,60	82,79
3 3/4"-4	4	3 3/4"	95,25	88,90	89,14
4"-4	4	4"	101,6	95,25	95,48