

**Gewinde-Tabelle Zollgewinde fein UNF 1 Zoll = 25,4 mm****Flankenwinkel 55°****© Land – Forsttechnik Walder**

Gewinde	Gänge je inch	Außendurchmesser		Kernlochdurchmesser in mm	
		inch	mm	Bolzen	Mutter
0-80	80		1,52	1,25	1,30
1-72	72		1,85	1,55	1,61
2-64	64		2,18	1,90	1,91
3-56	56		2,51	2,15	2,19
4-48	48		2,84	2,40	2,45
5-44	44		3,17	2,70	2,74
6-40	40		3,50	2,95	3,01
8-36	36		4,16	3,50	3,59
10-32	32		4,82	4,10	4,16
1/4"-28	28	1/4"	6,35	5,50	5,56
5/16"-24	24	5/16"	7,94	6,90	6,99
3/8"-24	24	3/8"	9,53	8,50	8,56
7/16"-20	20	7/16"	11,11	9,90	9,94
1/2"-20	20	1/2"	12,70	11,50	11,52
9/16"-18	18	9/16"	14,23	12,90	12,97
5/8"-18	18	5/8"	15,88	14,50	14,55
3/4"-16	16	3/4"	19,05	17,50	17,54
7/8"-14	14	7/8"	22,23	20,40	20,49
1"-12	12	1"	25,40	23,25	23,36
1 1/8"-12	12	1 1/8"	28,57	26,50	26,54
1 1/4"-12	12	1 1/4"	31,75	29,50	29,71
1 3/8"-12	12	1 3/8"	34,92	32,75	32,89

1 1/2"-12

12

1 1/2"

38,10

36,00

36,06